

LA-UR-21-31011

Approved for public release; distribution is unlimited.

Title: Detailed Validation of Ejecta Transport Models

Author(s): Ouellet, Frederick
Regele, Jonathan David

Intended for: Report

Issued: 2021-11-04

Disclaimer:

Los Alamos National Laboratory, an affirmative action/equal opportunity employer, is operated by Triad National Security, LLC for the National Nuclear Security Administration of U.S. Department of Energy under contract 89233218CNA000001. By approving this article, the publisher recognizes that the U.S. Government retains nonexclusive, royalty-free license to publish or reproduce the published form of this contribution, or to allow others to do so, for U.S. Government purposes. Los Alamos National Laboratory requests that the publisher identify this article as work performed under the auspices of the U.S. Department of Energy. Los Alamos National Laboratory strongly supports academic freedom and a researcher's right to publish; as an institution, however, the Laboratory does not endorse the viewpoint of a publication or guarantee its technical correctness.

Detailed Validation of Ejecta Transport Models

Frederick Ouellet and Jonathan D. Regele

PEM Mix and Burn FY 21 Update – October 21, 2021

X Computational Physics Division, Los Alamos National Laboratory

LANL Ejecta Experiments

- 2017 Experiments → study ejecta transport in inert and reactive gases
 - Solid ejecta
- 2019 Experiments → Repeat 2017 experiments with liquid ejecta
- Target thicknesses:
 - 2017 Tin: 2 mm
 - 2017 Cerium: 3 mm
 - 2019 Cerium: 1.75 mm




Figure 1: Figure 3 from [1] showing the ejecta experiment configuration and diagnostics

LANL Ejecta Experiments




Figure 2: Figure 6 from [2] shows ejecta velocities over time while propagating in a vacuum (left), an inert gas (center) and a reactive gas (right)

- Reacting ejecta show a staged rapid break-up phenomenon not seen otherwise
- Schwartzkopf and Schulz developed initial "0D" models of solid ejecta phenomena
 - did not account for spatial variations in gas or particle cloud temperatures

Overall goal for work:

1. Develop a 2D simulation to that enables accurate validation with experiments
2. Build a melt based break-up model on top of this 2D simulation and try to reproduce the new staged breakup behavior

Melt Dispersion Mechanism

- Searched aluminum combustion literature for analogous behaviors
- In the “melt dispersion mechanism” [3], if an initially solid particle melts at a fast heating rate while surrounded by an oxide shell, it will generate stresses which will fracture the shell and possibly cause cavitation due to an unloading wave
- Preliminary calculations using the physical constants for cerium and its hydride showed that this phenomenon, if present, may cause cavitation in the ejecta so long as $r_{ejecta} < 0.653 \mu m$

Table 1: Results from sample calculations used to determine the potential feasibility of cavitation in the ejecta particles from the experiments

Crystal Structure	M (C1)	$\delta(nm)$ (C1)	$P(t_s, R)$ (MPa)	$v(t_s, R)$ (m/s)	P_m (MPa)	v_m (m/s)	P_{cr} (MPa)	Cavitation?
CeF_2	2.9752	84.0290	365.953	85.464	-4679.546	240.095	-56.000	Yes
FeS_2	4.5678	54.7311	371.339	86.773	-4751.347	243.770	-56.000	Yes
AlB_2	3.8808	64.4192	362.940	84.732	-4639.369	238.038	-56.000	Yes
CeB_2	4.7389	52.7548	363.974	84.984	-4653.147	238.743	-56.000	Yes
$R_{max}(nm)$	652.733	-						

- Since, for us, the ejecta are initially liquid, but may form a crust afterwards, it is unclear how relevant this mechanism is.
 - Left open the possibility that this phenomenon could be occurring locally and cause the hydride shell to flake off rather than universally fracture

Particle Energy Equation: Numerical Stability

- Discovered a numerical stability issue in the implementation of the particle temperature update of the hydride model
- Tested with a single, small tin particle transporting in helium,
 - Initial method was semi-implicit:
$$\frac{\Delta e_p}{\Delta t} = \frac{Nu^n}{2} \frac{C^m}{\tau_T^n} (T_\infty^n - T_p^{n+0.5})$$
 - Writing this as $T_p^{n+1} = aT_\infty^n + bT_p^n$, an additional stability criterion was found by enforcing $a + b = 1$ and $a, b > 0 \rightarrow \Delta t < \frac{4\tau_T^n}{Nu^n}$
- Reformulated particle energy update with a fully implicit method





Figure 3: Temperature of a 1 μm diameter tin particle cooling in helium from 1183 K to 600 K without (left) and with (right) the semi-implicit time step restriction at various particle velocities

Slide 5

Hydrocode Governing Equations

Continuum Phase Governing Equations [3] → Discretized Staggered Mesh Equations

$$\rho \frac{d(\rho^{-1})}{dt} - \nabla \cdot (\mathbf{v}) = 0$$

$$\rho \frac{d\mathbf{v}}{dt} + \nabla P = 0$$

$$\rho \frac{de}{dt} + P \nabla \cdot (\mathbf{v}) = 0$$

Trivially satisfied

$$m_p \frac{d\mathbf{v}_p}{dt} + \sum_{Z(P)} \mathbf{f}_Z^p = 0$$

$$m_Z \frac{de_Z}{dt} - \sum_{P(P)} (\mathbf{f}_p^Z \cdot \mathbf{v}_p) = 0$$

Lagrangian Particle Equations:

$$\frac{dx_i}{dt} = \mathbf{u}_i$$

$$M_i \frac{d\mathbf{u}_i}{dt} = \mathbf{F}_{drag}$$

$$M_i C_i \frac{dT_i}{dt} = \dot{Q}_c$$

Additional Code Utilities:

- ALE relaxers to avoid mesh tangling
- Particles tracked as computational superparticles

Ejecta Models

- Ejecta Sourcing: Richtmyer-Meshkov Source Model [4]
 - Solves ODEs for bubble/spike velocities based on shock emerging from donor material and imparting a free-surface velocity to a perturbed surface
 - Ejecta velocities: Set to the spike tip velocity
 - Ejecta diameters: Based on perturbation wavelength and areal fraction of spikes on surface
 - Ejecta thermodynamic properties initialized by using values from target material 2 zones inward from sourcing face*

- Particle-Fluid Momentum Transfer: Parmar drag correlation

$$\mathbf{F}_{drag} = \frac{1}{8} \pi d_p^2 \rho_f |\mathbf{u} - \mathbf{v}| (\mathbf{u} - \mathbf{v}) C_D(Re_p, M_p)$$

- Formula for C_D given in [5]

- Particle-Fluid Heat Transfer: Hydriding model (currently minus the reaction term)

$$\dot{Q}_c = \dot{Q}_{conv} = \pi d_p k Nu (T_g - T_p)$$

$$Nu = 2 + 0.6 Re_p^{0.5} Pr^{\frac{1}{3}}$$

Modified Ejecta Initialization

- Early flyer plate test simulations with a geometry similar to the experiments showed an issue with the ejecta temperatures being reported from the simulations




Figure 4: Average ejecta temperatures for axisymmetric, 18 x 99 zone (left) and 36 x 198 zone (right) simulations

- No heat transfer → particle temperatures were constant after ejecta creation
- This led us to investigate the method being used to initialize certain ejecta properties

Modified Ejecta Initialization

- Originally, ejecta density, pressure, temperature and bulk modulus were all initialized to the values of the donor material in the zone immediately behind the generating face (i.e. $z=1$)
- A problem arises as these properties can be unphysical in simulations near a material interface
- Solution was to modify the code to make ejecta initialize these properties from a zone layer which is user-specified in the input deck
 - Exactly as existing treatment for shock speed and melt state calculations




Figure 5: Surface and wireframe contours of zonal temperatures $1\mu s$ after ejecta are produced at a tin target surface for illustration of zone depths

Modified Ejecta Initialization

- Results with new initialization were satisfactory and provided accurate ejecta temperatures





Figure 6: Average ejecta temperatures for axisymmetric, 36 x 198 zone (left) and 72 x 396 zone (right) simulations

- These changes have recently been merged into the main code repository

Simulation Setup and Initialization

- The target and flyer plate are both set to be tin.
- Flyer plate is used to avoid computationally modeling the HE from the experiments
- Flyer plate is initialized to the jump velocities reported in [2]
- The gas is initialized to the ambient state also reported in [2]




Figure 7: Simulation Configuration for 2017 Tin Cases

Simulation Matrix: Inert Experiment Comparisons

Table 2: Initial conditions for the ambient gases in the simulations for each case considered

Case	Gas	ρ_o (mg/cm^3)	P_o (KPa)	h_o (μm)	λ (μm)
SN3 - 2017	He	0.325	2.03	2.05	39.8
SN5 - 2017	He	1.520	9.45	2.05	40.6
SN6 - 2017	D_2	1.310	8.11	2.15	39.5
SN7 - 2017	D_2	0.327	2.03	2.20	43.8
CE3 - 2019	He	0.866	5.40	2.75	50.0

- SN 5/6 give comparisons to reported post-shock gas properties and jump velocities
- SN 5/6/7 are to compare results to LDV and IR imaging data from the experiments
 - Gives comparisons of ejecta velocities and temperatures
- CE 3 is meant to compare to Mie-Scattering experimental data for ejecta sizes

Grid Convergence Study

Table 3: Description of meshes used to study effect of grid refinement on simulated post-shock properties

Mesh	N_r	Δr (μm)	N_z	Δz (μm)	N_{tot}
1	360	69.5	102	614.2	36,720
2	540	46.3	152	412.2	82,080
3	792	31.5	210	298.3	166,320

- Early simulations using 2D-axisymmetric configurations show that $\frac{\Delta z}{\Delta r} \approx 9$ lead to the most stable runs
- Goal: Refine the initial mesh until simulations for Cases Sn5 and SN6 gave comparable post-shock gas conditions and jump velocities to those in [2]



Grid Convergence Study

Table 4: Simulation post-shock gas values and associated errors for Case SN5

	Buttler	M1	M2	M3	Error 1	Error 2	Error 3
$u_j (\frac{mm}{\mu s})$	1.920	1.927	1.923	1.920	0.39%	0.18%	0.01%
$\rho_{ps} (\frac{kg}{m^3})$	4.430	4.480	4.476	4.472	1.12%	1.04%	0.96%
$P_{ps} (MPa)$	9.500	9.492	9.461	9.435	-0.09%	-0.41%	-0.68%
$T_{ps} (K)$	1030.0	1027.2	1024.7	1022.6	-0.27%	-0.51%	-0.71%



- The 166,320 zone mesh was able to yield post-shock values within $\approx 1\%$ of the reported values (values from SN6 omitted for space)
- This mesh was chosen for the simulations discussed in the remainder of the talk

Simulation Contours – Case SN5



$$t = 80 \mu s$$

Simulation Contours – Case SN6



$$t = 0 \mu s$$

Velocimetry Comparison




Figure 8: Velocimetry plots from [2] for Cases SN5 and SN6

- Simulation underpredicts particle velocity at early times
- Reasonable comparison for most of simulated time

Radiance Temperature Comparison

- Major issue with comparing the simulations to experiments is the emissivity to use to convert the experimental T_R to the simulation particle temperatures
- Current guidance is that using $\epsilon \approx 0.5$ is a good estimate for liquid tin




Figure 9: Particle temperature plot along with transformed radiance temperatures from [2] for case SN5

- The simulation particle temperatures from SN5 agree well with radiance measurements under this assumption
- Case SN7 is currently post-processing and will be our second validation case

Ejected Mass and Size Comparisons

- We plan to compare simulation data to experimentally obtained ejecta size measurements to verify the ejecta sourcing model
- The comparison point for that will be simulation CE3, which is currently running
- Cloud averaged diameters are used for two of the finished runs (Fig. 10)
- Final comparison to experiments will be done at fixed heights corresponding to measurement locations





Figure 10: Average ejecta diameters over the entire cloud for simulations SN5 (left) and SN6 (right)

Conclusions

- Early project work focused on finding possible break-up mechanisms for the reactive ejecta and fixing some hydrocode stability issues
- Initial simulation work on replicating a subset of the experiments led to modifying the manner in which the thermodynamic properties of the ejecta were initialized in the code
- Preliminary comparisons of the simulated inert cases show ejecta velocities and temperatures with good agreement to reported experimental data
- Waiting for a few final simulations/comparisons before claiming that our simulation base is ready to proceed but current results are promising

Future Work

- Conclude verification of the inert simulations
 - Ejecta temperatures against radiance temperature measurements – SN7
 - Ejecta sizes against the experiments - CE3
 - This will confirm to us that the current simulation platform is ready to replicate the reactive experiments in a quantifiable manner
- Formulate melt-based break-up model for the transporting ejecta and implement the model into the hydrocode
- Run simulations of the reactive 2019 experiments and compare outputs to the reported diagnostics

